


PanelFix met 1-Cut-punt gegalvaniseerd



PanelFix met 1-Cut-punt verzonken kop

artikel nummer	maat	TX grootte	VE	artikel nummer	maat	TX grootte	VE
2600 35 030	3,5 x 30	15	1000	2600 50 040	5,0 x 40	25	200
2600 35 035	3,5 x 35	15	1000	2600 50 050	5,0 x 50	25	200
2600 35 040	3,5 x 40	15	1000	2600 50 060	5,0 x 60	25	200
2600 35 050	3,5 x 50	15	1000	2600 50 070	5,0 x 70	25	200
				2600 50 080	5,0 x 80	25	200
2600 40 030	4,0 x 30	15	500	2600 50 090	5,0 x 90	25	200
2600 40 035	4,0 x 35	15	500	2600 50 100	5,0 x 100	25	200
2600 40 040	4,0 x 40	15	500	2600 50 120	5,0 x 120	25	200
2600 40 045	4,0 x 45	15	500	2600 60 060	6,0 x 60	25	100
2600 40 050	4,0 x 50	15	500	2600 60 070	6,0 x 70	25	100
2600 40 060	4,0 x 60	15	200	2600 60 080	6,0 x 80	25	100
2600 40 070	4,0 x 70	15	200	2600 60 090	6,0 x 90	25	100
2600 40 080	4,0 x 80	15	200	2600 60 100	6,0 x 100	25	100
				2600 60 120	6,0 x 120	25	100
2600 45 035	4,5 x 35	25	500	2600 60 130	6,0 x 130	25	100
2600 45 040	4,5 x 40	25	500	2600 60 140	6,0 x 140	25	100
2600 45 045	4,5 x 45	25	500	2600 60 150	6,0 x 150	25	100
2600 45 050	4,5 x 50	25	500	2600 60 160	6,0 x 160	25	100
2600 45 060	4,5 x 60	25	200	2600 60 180	6,0 x 180	25	100
2600 45 070	4,5 x 70	25	200	2600 60 200	6,0 x 200	25	100
2600 45 080	4,5 x 80	25	200	2600 60 220	6,0 x 220	25	100
				2600 60 240	6,0 x 240	25	100
				2600 60 260	6,0 x 260	25	100
				2600 60 280	6,0 x 280	25	100
				2600 60 300	6,0 x 300	25	100

Uw voordeel: Lichte verwerking door optimale kracht-overbrenging
 Lager schroef koppel door wrijving onderdeel op schroefdraad
 Precisie aanzetten door boorpunt
 Gladde bovenkant door onderkop-freesribben
 Niet meer voorboren